350 Booklet System

SPECIFICATIONS

DC	C 11	1// 0:	COL	I ATO	ı

Number of Bins* 10, 20, 30, 40, 50, 60 (10 bins per tower)*

Paper Size¹ Width: 4.1" - 14"

Length: 5.8" - 24" (width of paper must be within 7.88" - 9.05"

when paper length is greater than 20")

Paper Weight Fine quality paper: 52 - 157gsm (Cover: 52 - 300 gsm) Art coated paper: 79 - 157gsm (Cover: 79 - 300 gsm)

Bin Capacity

Speed Bookletmaking: Up to 5,000 sets/hour** Collating: Up to 10,000 sets per hour**

Color Touch Screen LCD Panel (DSC-10/60i PC Controller software and Controller

IMBF are not compatible with the 350i Booklet System) 120V 60Hz 7.9 - 8.4A 910 - 960W Power

Dimensions (WxDxH) 34" x 33" x 78"

Weight

DSC-10/60D Bridge; LUR Lift Unit Right, D-Port Converter (required); Options

DBM-400STR Right Exit Deep Pile Stacker, DCR-ST Left Exit Cross Stacker; DCR-BP Bypass Bridge, DSC1060ENVLP Envelop Kit Weight

Other Features

* For 350i Booklet System, only 4 towers can be connected.

DBM-350 BOOKLETMAKER (Requires D-Port Converter)

CORNER/SIDE/TOP STITCHING APPLICATION

Sheet Size (Min./Max.) 10.12" x 7.17" - 11.69" x 8.5" Paper Capacity Up to 30 sheets***

SIGNATURE BOOKI FTMAKING APPLICATION Sheet Size (Min./Max.)

Paper Capacity Up to 22 sheets*** (maximum thickness: 2.1 mm/0.08") 64 - 127.9 gsm fine quality; 104.7 -127.9 gsm coated; cover - up Paper Weight

GENERAL Speed Up to 3,000 sets per hour** Detections

Wire draw detection Number of Stitcher Heads 2 Deluxe Stitch Heads standard. Can be upgrade to Hohner 43/6S.

5.82" x 8.27" - 12.6" x 18.11"

Saddle, corner, side, none (fold only) Stitch Positions

Programmable Memory Settings

Power Requirements

Automatic Functions Stitcher heads, back jogger, side guides, stitch stopper, fold stopper,

fold-back stopper positions, small booklet adjustments, fold roller gap, conveyance roller position, center reference, disengage the

operator side stitching head when corner stitching 100 to 240V 3.5 to 1.5 A 50/60 Hz

Dimensions (LxWxH) 72" x 26" x 41"

Weight 464 lbs.

Options

Corner Stitch Kit, Small Booklet Kit, 6 Page Insert Kit

Length: 7.17" - 8.50" (182 mm - 215.9 mm) CORNER STITCH KIT Width: 10.12 " - 11.69" (257 mm - 297 mm)

SMALL BOOKLET KIT Length: 9.45" - 16.93" (240 mm - 430 mm)

Width: 4.13" - 5.83" (105 mm - 148 mm)

6 PAGE INSERT KIT Length: Double letter (cover A3) Width: Letter (content A4)



5230 Finch Avenue East, Unit 6 Scarborough, ON M1S 4Z9 (416)297-7996 • (800)608-4506 www.printdigitalsolutions.com sales@printdigitalsolutions.com

DBM-350T TRIMMER (Requires D-Port Converter)

Trimming Mechanism Upper and lower shearing action Booklet Size (Min./Max.) 5.82" x 4.13" to 12.6" x 9.06" Trimmed Booklet Size (Min./Max.) 5.82" x 3.35" to 12.6" x 9.06" Trim Margin Up to 0.79"*** Up to 5,000 sets per hour** Speed Power Consumption Supplied by DBM-350 85" x 26" x 41" Dimensions (LxWxH) 155 lbs.

DBM-400STR STACKER (Requires D-Port Converter)

Sheet Capacity (Min./Max.) 8.25" x 5.5" to 13.77" x 19.68" Paper Capacity Up to 9,800 sets per hour** Speed Power Consumption 120V 60Hz 2.2A Dimensions (LxWxH) 30" x 35" x 35"

Automatic size change; 13 programmable memory

settings; straight or offset stacking; jam and door open

DSS-350 SQUARE SPINE (Requires D-Port Converter)

Up to 2,600 booklets per hour **Booklet Size** Max. 12.60" x 9.05" (320 mm x 230 mm) Min. 4.13" x 3.35" (105 mm x 85 mm) Paper Quality Fine Quality Paper: 64 - 127.9 gsm Art/Coated Paper: 104.7 - 127.9 gsm

Cover: Up to 300 gsm

Booklet Thickness Within 0.17'' / 4.2 mm (maximum 1 cover/ 210 gsm + 19

sheets/81.4 gsm) 25" x 26" x 32"

Dimensions (LxWxH) (626 mm x 662 mm x 817 mm)

DCR-ST CROSS STACKER (Requires D-Port Converter)

Paper Size (Min./Max.) Tray L - 8.46" x 12.60" to 13.98" x 17.72" Tray S - 8.27" x 12.80" to 5.83" x 9.84"

Tray L - 3.94" Stack Height Tray S - 7.87"

Tray L - 3,000 sets/hour 11" x 17"**

Tray S - 4,000 sets/hour 8.5" x 11"** Other Features Cross and straight stacking, adjustable set interval

Power Consumption 120V 60Hz 1.0A 28" x 27" x 25" Dimensions (LxWxH)

Main unit - 97 lbs. Tray L - 18 lbs.

Tray S - 18 lbs. Note: Requires DCR-BP Bypass Conveyor when using in-line with bookletmaker

COMMON SYSTEM CONFIGURATIONS (Additional components may be required)

• DSS-350 + DBM-350T + DBM-350 + LCD + DSC-10/60i

• DSS-350 + DBM-350T + DBM-350 + DCR-BP + DCR-ST + LCD + DSC-10/60i

• DSS-350 + DBM-350T + DBM-350 + LCD + DSC-10/60i + LUR + DBM-400STR

(D-Port Convert required for the following machines: DSS350, DBM350T, DBM350, DCR-ST, DBM400STR) Options: DSS-350, DCR-BP DCR-ST, DBM400STR

Production rates are based on optimal operating conditions and may vary depending on stock and environmental conditions. As part of our continuous product im program, specifications are subject to change without notice.

*** Dependent upon paper weight and size

Duplo USA Corporation

Duplo

3050 S. Daimler Street, Santa Ana, CA 92705 (949) 752-8222 (800) 255-1933 (949) 851-3054 fax www.duplousa.com All rights reserved. No part of this document may be produced without permission of Duplo USA Corporation.



350 Booklet System

Mid-Range Production Bookletmaking



¹ Max. sheet size is depending upon the specification of the bookletmaker and other connecting devices

^{**} Dependent upon connected devices and number of bins in use

id-Range Collating & Bookletmaking System

The 350 Booklet System is Duplo's mid-range collating and bookletmaking system, integrating the DSC-10/60i Suction Collators with the DBM-350 Bookletmaker. With a production speed of up to 3,000 booklets per hour, the system produces a wide range of offset and digital print applications, from calendar and catalogs to brochures and newsletters, on demand. The 350 Booklet System provides the efficiency to deliver jobs in shorter turnarounds and its modular design offers users the flexibility to customize them according to their needs.

THE COLLATOR ADVANTAGE

With a variety of finishing solutions in the market today, off-line collating continues to maintain significant advantages over inline systems. Jobs processed on a collating and bookletmaking system are finished at much faster speeds and output from multiple printers can be accepted and finished with equal ease. Should the printer break down, an off-line finishing operation will continue to run without interruption.

FAST AND EASY CHANGEOVERS

The 350 Booklet System is very easy to use. Jobs can be quickly programmed and saved via the LCD Control panel. Up to 20 jobs can be saved and recalled to allow for fast set-up and changeover, with little or no adjustment.

DSC-10/60i SUCTION COLLATORS: SUPERIOR FEEDING SYSTEM

The 350 Booklet System utilizes Duplo's DSC-10/60i Suction Collators. The unique 8-belt air suction feed system along with an Air Management System make these collators the most reliable in the industry. Incorporating Duplo's patented dual fan technology, each bin comes equipped with two individual fans - one to produce a stable flow of air separation and the other to generate consistent suction for feeding. With adjustments conveniently located beside each bin, the Air Management System enables operators to easily fine-tune the amount and strength of air, if necessary.

High resolution optical sensors add an extra level of reliability by ensuring miss or double feed errors are identified. Faulty sets are diverted into a reject tray to allow continuous operation and can easily be recovered by simply correcting and inserting them into the hand marry station.

The 350 Booklet System can be configured with up to 4 towers for a total of 40 bins. The DSC-10/60i Collators offer flexibility for various application needs including Interleaf Mode to insert single or double sheets into the booklet.

As sheets are collated in the DSC-10/60i Collator, sets are delivered into the DBM-350 Bookletmaker for stitching, folding, and trimming. Booklets are smoothly guided through the stitching section by the push belt transport system and only activates when the book is ready to move, thus preventing marks and static build up. The bookletmaker utilizes heavyduty Deluxe 26D stitch heads for durable, quality stitching and features a programmable spine compressor to flatten the spine

VALUE ADDED OPTIONS

Customize the 350 Booklet System to meet your needs.

• Face trim booklets with the DBM-350T Trimmer.

• Produce various applications with small booklet, side/corner stitch, and 6-page insert kits.

• Give booklets a flat, square spine finish with the DSS-350 Square Spine module.

• Perform collating and stacking jobs with the DCR-ST Cross Stacker.

* Please note: The DSC-10/60i PC Controller software is not compatible with the 350 Booklet System.



for a lay-flat finish.

The 2.6" bin capacity supports a variety of paper stocks 52–300 gsm and paper sizes ranging from 4.1" x 5.8" to 14" x 24".



8-belt air suction feed system and Air Management System ensure reliable feeding.

LUR Bridge

DBM-350 BOOKLETMAKER: CUSTOMIZABLE TO MEET YOUR NEEDS

The modular design of the system enables users to configure it with a number of options such as small booklet, side/corner stitch, and 6-page insert kits to meet various application demands. Booklets can be faced trimmed by adding the DBM-350T Trimmer. As booklets are trimmed and delivered onto the stacker, waste is automatically deposited into an external bin and can be easily removed while the system is running, ensuring non-stop productivity.

Deliver booklets with a flatter, square spine finish by adding the DSS-350 Square Spine module and add value to the finished book. With a processing speed of up to 2,600 booklets per hour, the DSS-350 is the fastest of its kind and can be connected inline with the 350 Booklet System.

COLLATING AND STACKING

Perform collating and stacking jobs with the optional DCR-ST Cross Stacker. Placed between the collator and bookletmaker, the DCR-ST can cross or straight stack up to 7.87". When the stacker is not in use, a bypass bridge redirects the sheets into the bookletmaker for bookletmaking jobs without having to remove any devices.

DBM-400STR Stacker



DCR-ST Cross Stacker



LUL-HM Hand Marry

The integrated