



TITAN[®] 200BC
with manual backgauge

TITAN[®] 200



**ASSURANCE YOU MADE
THE RIGHT DECISION**

TITAN[®] 200 & 200BC

Capitalizing on Challenge's time-proven expertise in manufacturing paper cutters, the TITAN[®] 200BC and 200 are engineered and manufactured to the highest of safety standards available.



200BC with manual backgauge



200

FEATURES AND BENEFITS

- 20" Cutting Width - 3-1/4" clamp opening
- Hydraulic Cutting & Clamping
- Adjustable Clamp Pressure
- Cutting Area Protection - Plexiglas safety shield
- Plexiglas Rear Table Safety Cover
- Two-Hand Cut Buttons
- Light Line Cut Position Indicator
- Manually Controlled Backgauge with Lock
- Energy Efficient - Motor runs only when cutting
- Heavy Duty Casters For Portability
- Rugged Steel & Cast Iron Construction
- 12" x 19" / 30.5 cm x 48 cm Side tables (optional)

SPECIFICATIONS

- Cutting Width: 20"/50.8 cm
- Clamp Opening:
without false clamp plate 3-1/4"/8.3 cm
with false clamp plate 3"/7.6 cm
- Minimum Cut:
without false clamp plate: 1/2"/13mm
with false clamp plate: 1-7/8" /48mm
- Maximum Cut Depth: 20"/50.8 cm
- Table Space In Front of Knife: 16"/40.6 cm
- Table Space Behind Knife: 20"/50.8 cm
- Table Height: 36"/91.4 cm
- Overall Height: 53"/135 cm
- Overall Width: 36"/91.4 cm
- Overall Length: 50-7/8"/129.3 cm
- Will Pass Through Opening:
minimum required 36-1/4"/92.1 cm
table, treadle & front shield off 29"/73.7 cm
- Net Weight: 755 lbs /343 kg
- Shipping Weight (approximate): 980 lbs/444 kg



(416)297-7996 • (800)608-4506

FEATURES AND BENEFITS

- 20" Cutting Width - 3-1/4" clamp opening
- Hydraulic Cutting & Clamping
- Adjustable Clamp Pressure
- LED Line Light Cut Position Indicator
- Cutting Area Protection - Plexiglas safety shield
- Plexiglas Rear Table Safety Cover
- Two-Hand Cut Buttons
- Programmable Controlled Backgauge
- Energy Efficient - Motor runs only when cutting
- Heavy Duty Casters For Portability
- Rugged Steel & Cast Iron Construction
- 12" x 19" / 30.5 cm x 48 cm Side Tables (optional)
- Optional Challenge Exclusive - Ergo-Touch Cut Buttons

SPECIFICATIONS

- Cutting Width: 20"/50.8 cm
- Clamp Opening:
without false clamp plate 3-1/4"/8.3 cm
with false clamp plate 3"/7.6 cm
- Minimum Cut:
without false clamp plate: 1/2"/13mm
with false clamp plate: 1-7/8" /48mm
- Maximum Cut Depth: 20"/50.8 cm
- Table Space In Front of Knife: 15-1/4"/39 cm
- Table Space Behind Knife: 20"/50.8 cm
- Table Height: 36"/91.4 cm
- Overall Height: 53"/134.6 cm
- Overall Width: 36"/91.4 cm
- Overall Length: 49-5/8"/126 cm
- Will Pass Through Opening:
minimum required 36-1/4"/92.1 cm
table, treadle & front shield off 29"/73.7 cm
- Net Weight: 800 lbs /363 kg
- Shipping Weight (approximate): 980 lbs/444 kg

ELECTRICAL CE

- 1-1/2 HP, Single-Phase, 60 Hz, 230 Volts, AC, 12 Amps.
- Power cord included
- Service Size 15 Amps
- Requires receptacle type: NEMA 6-15R

www.printdigitalsolutions.com

ADV031/GPCO/0811/2M